

# **SAFETY DATA SHEET**

Issue Date 31-Jan-2013 Revision Date 05-Apr-2013 Version 1

# 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier** 

Product Name Lifetime PRO Sealant

Other Means of Identification

**SDS** # RD-0097

Product Code 0856PR Series

Recommended Use of the Chemical and Restrictions on Use

**Recommended Use** Aqueous White Sealant w/ Silicone (White & Colors).

**Details of the Supplier of the Safety Data Sheet** 

Supplier Address Red Devil, Inc. 4175 Webb Street Pryor, Oklahoma 74361 www.reddevil.com

**Emergency Telephone Number** 

Company Phone Number 918-825-5744

Fax: 918-825-5761

Emergency Telephone INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

# 2. HAZARDS IDENTIFICATION

### Classification

This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The product contains no substances which at their given concentration, are considered to be hazardous to health

Appearance White and colored paste Physical State Smooth paste Odor Mild acrylic

Revision Date 05-Apr-2013

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Calcium Carbonate	1317-65-3	<55
Acrylic Emulsion	MIXTURE	<30
Benzoate Ester	Proprietary	<8
Titanium dioxide	13463-67-7	<2
Non-hazardous Ingredients*	Proprietary	<5
Carbon Black	1333-86-4	0-0.25
Ammonium Hydroxide	7664-41-7	<0.25
Petroleum Hydrocarbon	64742-48-9	<0.75

<sup>\*</sup> Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). (Calcium Carbonate, Titanium Dioxide) Inhalation of particulates unlikely due to product's physical state. (Carbon Black) May be present in colors other than White.

# 4. FIRST AID MEASURES

#### **First Aid Measures**

**General Advice** Provide this SDS to medical personnel for treatment.

**Inhalation** Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains

difficult, get medical attention.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Seek immediate medical attention/advice.

**Ingestion** Do not induce vomiting, unless directed by medical personnel. Get immediate medical

attention. If vomiting occurs, keep head low so that stomach content does not get into the

lungs.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If irritation persists, seek medical attention.

### Most Important Symptoms and Effects, both Acute and Delayed

Symptoms Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact

with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and

sneezing.

# Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physicians Provide general supportive measures and treat symptomatically. May aggravate

pre-existing skin disorders.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Water spray (fog). Foam.

Unsuitable Extinguishing Media Not determined.

RD-0097 - Lifetime PRO Sealant Revision Date 05-Apr-2013

#### Specific Hazards Arising from the Chemical

Product is combustible & may ignite if exposed to high temperature or direct flame.

**Hazardous Combustion** 

**Products** 

Carbon, titanium & iron oxides, depending upon formulation.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool.

# 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

For Emergency Responders Restrict access to spill area.

**Environmental Precautions** Minimize use of water to prevent environmental contamination. Prevent spill or rinse from

contaminating storm drains, sewers, soil or groundwater.

### Methods and Material for Containment and Cleaning Up

Methods for Containment Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill.

Methods for Cleaning Up Sweep up absorbed material and shovel into suitable containers for disposal. Wash area

with soap and water. For waste disposal, see section 13 of the SDS.

# 7. HANDLING AND STORAGE

### **Precautions for Safe Handling**

Advice on Safe Handling Avoid breathing vapors. Use only with adequate ventilation. Open windows & doors to

ensure fresh air cross-ventilation during application and curing. Wash thoroughly with soap and water after handling. Avoid contact with skin, eyes or clothing. While handling product

keep out of reach of childrens and pets.

### Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions Close container after each use. Store containers away from excessive heat & freezing. Do

not store @ temperatures above 120 ° F. To maximize shelf life, store @ temperatures

below 26C (80F).

Incompatible Materials Oxidizers. Strong acids.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Exposure Guidelines** Exposure guidelines / protective equipment are for routine handling and accidental spills

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate 1317-65-3	-	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
		(vacated) TWA: 15 mg/m³ total	5
		dust	
		(vacated) TWA: 5 mg/m <sup>3</sup>	
		respirable fraction	
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7	_	(vacated) TWA: 10 mg/m³ total	
		dust	

\_\_\_\_\_

Carbon Black	TWA: 3 mg/m³ inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup>
1333-86-4		(vacated) TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
			TWA: 0.1 mg/m³ Carbon black in
			presence of Polycyclic aromatic
			hydrocarbons PAH
Ammonium Hydroxide	STEL: 35 ppm	TWA: 50 ppm	IDLH: 300 ppm
7664-41-7	TWA: 25 ppm	TWA: 35 mg/m <sup>3</sup>	TWA: 25 ppm
		(vacated) STEL: 35 ppm	TWA: 18 mg/m <sup>3</sup>
		(vacated) STEL: 27 mg/m <sup>3</sup>	STEL: 35 ppm
			STEL: 27 mg/m <sup>3</sup>

### **Appropriate Engineering Controls**

Engineering Controls Ventilation must be adequate to maintain the ambient workplace atmosphere below the

exposure limit(s) outlined in the SDS.

### Individual Protection Measures, such as Personal Protective Equipment

regulations & standards.

Skin and Body Protection Skin: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill

response. If necessary, refer to appropriate regulations & standards.

Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment) or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations &

standards.

**Respiratory Protection** If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below

19.5% considered IDLH by OSHA. In such instances, use full-facepiece pressure demand SCBA or a full facepiece, supplied air respirator w/ auxillary self-contained air supply.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

Physical State Smooth paste

AppearanceWhite and colored pasteOdorMild acrylicColorMulti-colorOdor ThresholdNot determined

Property Values Remarks • Method

**pH** 7.0-10.0

Melting Point/Freezing Point < 0 °C / <32 °F

Boiling Point/Boiling Range Not Established

Flash Point > 93.33 °C / > 200 °F

Evaporation Rate

Flammability (Solid, Gas)
Upper Flammability Limits
Lower Flammability Limit

Vapor Pressure

Not determined
Unknown
Unknown
Not established

Vapor Pressure
Vapor Density
Specific Gravity
Not established
Heavier than air
~1.55-1.65

Water Solubility
Solubility in Other Solvents
Partition Coefficient
Autoignition Temperature
Decomposition Temperature
Soluble in water
Not determined
Unknown
Not determined

@ 25 °C (77 °F)

·

Kinematic Viscosity

Dynamic Viscosity

Explosive Properties

Oxidizing Properties

Not determined

Not determined

Not determined

**VOC Content (%)** <1.5%

# 10. STABILITY AND REACTIVITY

### Reactivity

Cures upon contact with air.

#### **Chemical Stability**

Stable under recommended storage conditions.

### **Possibility of Hazardous Reactions**

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

#### **Conditions to Avoid**

Incompatible Materials. Excessive heat or cold.

### **Incompatible Materials**

Oxidizers. Strong acids.

### **Hazardous Decomposition Products**

Thermal decomposition can generate irritating dust, fumes and toxic gases (carbon, titanium, and iron oxides, depending upon formulation).

# 11. TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

#### **Product Information**

**Inhalation** Mildly irritating to respiratory tract.

**Eye Contact** May cause temporary irritation on eye contact.

Skin Contact Prolonged and frequent contact may cause redness and irritation. Repeated skin contact

may cause dermatitis.

Ingestion May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

#### **Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg(Rabbit)	-
Ammonium Hydroxide 7664-41-7	= 350 mg/kg ( Rat )	-	= 5.1 mg/L (Rat) 1 h = 2000 ppm (Rat) 4 h
Petroleum Hydrocarbon 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-

### Information on Physical, Chemical and Toxicological Effects

**Symptoms** Please see section 4 of this SDS for symptoms.

RD-0097 - Lifetime PRO Sealant Revision Date 05-Apr-2013

# Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

**Sensitization** Not known to be human skin or respiratory sensitizers.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Trace residual Formaldehyde present in base emulsion viewed as possible cancer hazard. Carbon black is a possible carcinogen when it appears as a respirable dust.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X
Carbon Black 1333-86-4	A3	Group 2B		Х

IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans

#### **Numerical Measures of Toxicity**

Not determined

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

PRACTICES SHOULD BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

Product not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Carbon Black 1333-86-4				5600: 24 h Daphnia magna mg/L EC50
Ammonium Hydroxide 7664-41-7		0.44: 96 h Cyprinus carpio mg/L LC50 0.26 - 4.6: 96 h Lepomis macrochirus mg/L LC50 1.17: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.73 - 2.35: 96 h Pimephales promelas mg/L LC50 5.9: 96 h Pimephales promelas mg/L LC50 static 1.5: 96 h Poecilia reticulata mg/L LC50 1.19: 96 h Poecilia reticulata mg/L LC50 static 1.5: 96 h		25.4: 48 h Daphnia magna mg/L LC50
Petroleum Hydrocarbon 64742-48-9		2200: 96 h Pimephales promelas mg/L LC50		2.6: 96 h Chaetogammarus marinus mg/L LC50

# Persistence and Degradability

Not tested for persistence & biodegradability

#### **Bioaccumulation**

Not tested for bio-accumulation potential

### **Mobility**

Not tested for mobility in soil

NOT LESTED FOR THOUSING HT SOIL				
Chemical Name	Partition Coefficient			
Ammonium Hydroxide	-1.14			
7664-41-7				

# **Other Adverse Effects**

Environmental Exposure Controls: Should be maintained so as to prevent release to the environment (atmospheric release, release to waterways & spills)

\_\_\_\_\_\_

RD-0097 - Lifetime PRO Sealant Revision Date 05-Apr-2013

#### Ozone

Not expected to produce any ozone depletion

# 13. DISPOSAL CONSIDERATIONS

### **Waste Treatment Methods**

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

US EPA Waste Number Not applicable.

# 14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including

exemptions and special circumstances.

**DOT** Not regulated

IATA Not regulated

IMDG Not regulated

# 15. REGULATORY INFORMATION

# **International Inventories**

Not Determined

TSCA Listed
DSL Listed
NDSL Listed

# Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

# US Federal Regulations

### **SARA 313**

Not determined

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ammonium Hydroxide - 7664-41-7	7664-41-7	<0.25	1.0

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard No

Sudden release of pressure hazard No Reactive Hazard No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ammonium Hydroxide	100 lb			X
7664-41-7				

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ammonium Hydroxide	100 lb	100 lb	RQ 100 lb final RQ
7664-41-7			RQ 45.4 kg final RQ

### **US State Regulations**

Chemical Name	California Proposition 65	
Titanium dioxide - 13463-67-7	Carcinogen	
Carbon Black - 1333-86-4	Carcinogen	

# U.S. State Right-to-Know Regulations

Not Determined

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Carbon Black 1333-86-4	X	X	X
Ammonium Hydroxide 7664-41-7	Х	X	Х

# **16. OTHER INFORMATION**

<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	1	1	0	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	1	0	Not determined

Issue Date31-Jan-2013Revision Date05-Apr-2013Revision NoteNew format

# **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**